

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: SONAPEN VP650+

Use / description of product: A solvent removable, visible Red Dye Penetrant for use in the Dye Penetrant Inspection Process BS EN ISO 571-1:1997 (BS EN ISO 3452-2:2000 Sensitivity level 2).

Company name: Sonatest Ltd
Dickens Rd
Old Wolverton
Milton Keynes
Bucks
MK12 5QQ
United Kingdom
Tel: +44 (0)1908 525 910
Fax: +44 (0)1908 321 323

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: KEROSENE - UNSPECIFIED - DISTILLATES (PETROLEUM),
HYDROTREATED LIGHT 50-70%
EINECS: 265-149-8 CAS: 64742-47-8
[Xn] R65; [N] R51/53; [Xi] R66

- RED DYE CONCENTRATE (FOR HYDROCARBON DISPERSION) 1-10%
[-] R10; [Xn] R20/21; [Xi] R38; [Xn] R62
- LIQUID FLOW ENHANCER 1-10%
CAS: 2217-35-8
[Xn] R22; [Xi] R36/37/38
- CO2 1-10%
EINECS: 204-696-9 CAS: 00124-38-9

3. HAZARDS IDENTIFICATION

Main hazards: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.
Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness with prolonged contact

Eye contact: There may be irritation and redness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water. Remove contaminated clothing, including shoes, and launder before re-use.

SAFETY DATA SHEET

SONAPEN VP650+

Eye contact: Bathe the eye with running water for 15 minutes. If irritation persists get medical assistance.

Ingestion: Do not induce vomiting. Keep at rest. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious, check for breathing and apply artificial respiration if necessary. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Foam Dry chemical powder. Water spray. Use water spray to cool surfaces exposed to fire and protect personnel.

Exposure hazards: Containers may explode if exposed to fire.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Use absorbant granules as required. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

7. HANDLING AND STORAGE

Handling requirements: Smoking is forbidden. Do not use near sources of ignition. Use good hygenic practice and housekeeping methods.

Storage conditions: Store in cool, well ventilated area. Keep away from sources of ignition. Keep away from direct sunlight. Store in dry conditions.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Hazardous ingredients: KEROSENE - UNSPECIFIED - DISTILLATES (PETROLEUM),
HYDROTREATED LIGHT
TWA 1000mg/m3 (manufact)

- CO2
TWA 5000PPM STEL 15000PPM

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection should not be necessary during normal use.

Hand protection: Butyl gloves. Nitrile gloves. Gloves (oil-resistant).

Eye protection: Safety glasses/goggles are recommended.

Skin protection: Overalls recommended. No special protection other than hands.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Aerosol

Colour: Red

Odour: Perceptible odour

Solubility in water: Not miscible

Viscosity: Non-viscous

Viscosity value: 3.5cSt

Flash point°C: >100

Relative density: 0.84

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to avoid: Hot surfaces. Heat. Sources of ignition.

Materials to avoid: Strong oxidising agents. Natural rubbers, polystyrene and butyl rubbers Will permanently stain materials, painted surfaces and other coatings.

Haz. decomp. products: None

11. TOXICOLOGICAL INFORMATION

Chronic toxicity: Frequent or prolonged contact may irritate and cause skin dryness, cracking and dermatitis.

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Insoluble in water. Floats on water. This product is not classified as a Volatile Organic Compound according to the directive 99/13/EC.

Persistence and degradability: Rapidly biodegradable. Aerobically biodegradable.

Bioaccumulative potential: No data available.

Other adverse effects: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal operations: Full aerosol cans must be disposed of as hazardous waste. Empty aerosol cans should be disposed of in accordance with local authority regulations. Best disposal practice would be depressurisation of can and incineration of liquid product. Manufacturer can advise on recovery.

Disposal of packaging: Empty aerosols can be recycled. Packaging card and plastics can be recycled.

SAFETY DATA SHEET

SONAPEN VP650+

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1950 **ADR Class:** 2
Classification code: 5F
Shipping name: AEROSOLS
Labelling: 2.1



IMDG / IMO

UN no: 1950 **Class:** 2
EmS: F-D,S-U **Marine pollutant:** .
Labelling: 2.1

IATA / ICAO

UN no: 1950 **Class:** 2
Labelling: 2.1

15. REGULATORY INFORMATION

Hazard symbols: Harmful.
 Dangerous for the environment.



Risk phrases: R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.

Safety phrases: S3/9/14: Keep in a cool, well ventilated place away from ...

S23: Do not breathe ...

S24/25: Avoid contact with skin and eyes.

S35: This material and its container must be disposed of in a safe way.

S36/37: Wear suitable protective clothing and gloves.

S38: In case of insufficient ventilation, wear suitable respiratory equipment.

SAFETY DATA SHEET

SONAPEN VP650+

S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

S62: If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Precautionary phrases: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Water hazard class:

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. OTHER INFORMATION

Risk phrases used in s.2: R65: Harmful: may cause lung damage if swallowed.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.
R10: Flammable.
R20/21: Harmful by inhalation and in contact with skin.
R38: Irritating to skin.
R62: Possible risk of impaired fertility.
R22: Harmful if swallowed.
R36/37/38: Irritating to eyes, respiratory system and skin.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.